

Cocoon™ Cellulose Insulation

Manufacturer:

U.S. Green Fiber LLC

Sacramento, CA

800-655-9754

www.us-gf.com

Attributes:

Cellulose insulation has several environmental advantages over other insulating materials. In terms of resources, most cellulose insulation contains 75%-80% post-consumer recycled newspaper and a non-toxic borate and/or ammonium sulfate fire retardant. The energy performance of cellulose is comparable to high-density fiberglass batts at roughly R-3.7/in. Cellulose insulation can be loose-filled into attic spaces, sometimes in a stabilized form to resist settling. For vertical applications cellulose is most effectively installed as a wet-spray product with a water-activated adhesive or densely packed to prevent settling.

Local source(s):

Home Depot

Rohnert Park • 585-9200

Friedman Brothers Home Improvement Centers

Santa Rosa • 584-7811

Sonoma • 939-8811



Eco-shake™ Roofing Shingles

Manufacturer:

Re-New Wood, Inc.

Wagoner, OK

800-420-7576

www.renewwood.com

Attributes:

Made from 100% recycled wood and plastic (the plastic is 80% post-consumer).

Available in wood shake.

50 year warranty.

Local source(s):

See manufacturer information above



Safecoat DinoSeal™

Manufacturer:

**American Formulating
& Manufacturing**

San Diego, CA

800-239-0321

www.afmsafecoat.com

Attributes:

DynoSeal™ is an asphaltic emulsion waterproof sealer with a VOC content of less than 100 g/l for use on roofs, foundations, and other wet applications. The product containers have over 90% post-consumer recycled plastic content. The Dyno line of AFM coatings also includes driveway sealers and UV-stabilized rooftop coatings.

Local source(s):

The Ecology Center
Berkeley, CA • 510-548-3402

